



Zhejiang Dejia New Material Co.,Ltd.

#1 Luhong Road, Qianjiang Industrial Zone, Haining
City,Zhejiang Province,314413,P.R.China

Tel: +86 573 877 99 855 Fax: +86 573 877 99 811

Website: www.dejiafabric.com Email: roy@dejiafabric.com

TECHNICAL DATA SHEET

Product: PVC Coated Boat Material (DCW850)

Application:

PROPERTIES	TEST METHOD	METRIC
Support Cloth	(DIN 6000)	Polyester
Specification	(DIN EN 1049-2)	23*23 per inch
Yarn (dtex)	(DIN EN ISO 2060)	1000*1000 D
Type of Coating	PVC coated on both sides	
Total Weight	(DIN EN ISO 2286-2)	850g/m2
Width	(DIN EN ISO 2286-1)	1.02~3.20M
Tensile strength	(DIN 53354)	3500/3000 N/5CM
Tear strength	(DIN 53356)	360/350 N
Low Temperature-No Crack At		-40°C
Adhesion		130 N/5CM min

Available width: from 1.02m~3.20m

Packing: Craft paper or transparent film

Features:

- A: Glossy/Matt surface
- B: UV resistant
- C: Anti-mildew; anti-fungus available
- D: High tenacity polyester yarn ensures superior durability
- E: Strong, smooth, lightweight flexible material

Note: Information listed above is based on our general experience and observation and is given in good faith. Dejia will not accept any responsibilities with respects to factors outside our knowledge. Values without tolerance statements are values with a tolerance of +/-5%.